SW405K

PRODUCT SPECIFICATIONS





STANDARD FEATURES

- Engine: Deutz TCD 7.8
- Boom suspension system
- Differential Locking Axle
- Automatic Transmission Kick Down
- Bucket Self-Leveling and Return to Dig
- Single joystick control
- Third Function Hydraulics
- Reversible fan
- Rear view camera

- Net Power195 kW / 262 hp
- Bucket Capacity
 3.0 m³
- Operating Weight 18,500 kg
- Full Turn Tipping Load
 13100 kg

YELLO EQUIPMENT


SANY AU THORISED DEALER


P: 1300 093 556 W: YELLO EQUIPMENT.CO



PRODUCT SPECIFICATIONS

DIMENSIONS





OVERALL DIMENSIONS

		METRIC	STANDARD
1	Height to Axle Centerline	440 mm	17"
2	Height to Top of Cab	3527 mm	139"
3	Center Line of Rear Axle to Edge of Counterweight	2330 mm	92"
4	Wheelbase	3200 mm	10' 6"
5	Center Line of Front Axle to Center Pivot	1600 mm	63"
6	Shipping Length without Attachment	6862 mm	22' 6"
7	Shipping Length with Bucket	8142 mm	26' 8"
8	Max. Dump Height	5441 mm	17' 10"
9	Hinge Pin Height at Max. Lift	4133 mm	13' 6"
10	Dump Clearance at Max. Lift	3118 mm	10' 3"
11	Dig Depth, Level Bucket	56 mm	2.2"
12	Reach at Max. Lift and 45° Discharge	1140 mm	45"
13	Roll Back at Max. Lift	5	8°
14	Dump Angle at Max. Lift and Dump	4.	5°
15	Roll Back at Carry Height		
16	Roll Back at Ground	4.	5°
17	Tail Angle to the Rear Wheel	2	7°
18	Clearance Circle to Outside of Tires	5800 mm	19'
19	Clearance Circle to Counterweight	5911 mm	19' 5"
20	Max. Circle	6456 mm	21' 2"
21	Width of the Bucket	3000 mm	9' 10"
22	Width	2200 mm	87"
21	Articulation Angle	+/-	40°

Machine Parameters

Engine	
Engine Model	Deutz TCD7.8
Max Gross Power	195 kW
Net Engine Power	188 kW
Max Gross Torque	436 ft kg
Displacement	7.8 ltr

Operating	
Bucket Capacity	3.2 m3
Breakout Force	18,000 kg
Tipping Load Straight	14,500 kg
Tipping Load @ Full Turn	13,100 kg
Clearance (full lift 45° dump)	3109 mm
Reach (full lift 45° dump)	1168.4 mm

Weight	
Operating Weight	18,500 kg

Hydraulic System	
Max Flow	368 L/pm
Max Pressure	275.32 kg/cm2

Hydraulic Cycle Times	
Raise	5.4 sec
Dump	1.9 sec
Float Down	3.3 sec
Total Cycle Time	10.6 sec

Service Capacities	
Fuel Tank	321.76 L
Cooling System	19.87 L
Engine Crankcase	22.71 L
Transmission	17.79 L
Front Axle	18.92 L
Rear Axle	18.92L
Hydraulic Tank	117.34 L
DEF Tank	39.74 L

Transmission	
Shift Modes	Automatic, Manual, Kick Down
Forward Gear 1–4	6-40 kph
Reverse Gear 1–4	6–25 kph

Power Train	
Front Axle	Fixed
Traction Aid	Manual Differential Lock
Rear Axle	Oscillating
Traction Aid	Open Differential
Service Brakes	Wet Disk
Parking Brake	Disk Brake

YELLO EQUIPMENT

P: 1300 093 556 W: YELLO EQUI PMENT. CO M

