# SMHC45

# PRODUCT SPECIFICATIONS





### STANDARD FEATURES

- Proven Reliability
- Wide Working Range
- High Efficiency
- Low Fuel Consumption
- ISUZU engine
- Advanced Structure Design
- Working Reach 5m to 11.9m
- Smart Controller Features

- **Rated Power** 212 kW /2000 rpm
- Working Height up to 18m
- **Overall Weight** 45,200 kg
- Gradeability

#### YELLO EQUIPMENT

SANY AUTHORISED DEALER

P: 1300 093 556 W: YELLOEQUIPMENT.COM

YELLC **EQUIPMENT** 

## SWHC45 PRODUCT SPECIFICATIONS

#### **Brief Introduction**

Sany 45t Material Handling machine mainly apply to grab and loading or unloading operation for waste steel and bulk, with high efficiency, super high performance, safety and reliability.



#### **CONFIGURATION PARAMETER**

| Power<br>system               | Engine                                                   | Maximum power                           | 212kW/2000rpm                              |                          |                         |                          |  |
|-------------------------------|----------------------------------------------------------|-----------------------------------------|--------------------------------------------|--------------------------|-------------------------|--------------------------|--|
|                               |                                                          | Maximum torque                          |                                            | 1080Nm//1500rpm          |                         |                          |  |
|                               |                                                          | Emission                                | CHN III                                    |                          |                         |                          |  |
|                               |                                                          | Oil tank                                | 540L                                       |                          |                         |                          |  |
| Moving system                 | Working                                                  | 2590mm                                  |                                            |                          |                         |                          |  |
|                               | Tread width                                              |                                         | 4140mm                                     |                          |                         |                          |  |
|                               | Track width                                              |                                         | 600mm                                      |                          |                         |                          |  |
|                               | Maximum travel speed                                     |                                         | 5km/h                                      |                          |                         |                          |  |
| Hydraulic system              | Contro                                                   | Electronic control positive flow system |                                            |                          |                         |                          |  |
|                               | Main pump                                                | Model                                   | Kawasaki K5V160DTH1SXR-9T46-BV             |                          |                         |                          |  |
|                               |                                                          | Rated flow                              | 2X320L/min                                 |                          |                         |                          |  |
|                               | Main valve                                               |                                         | Kawasaki KMX15RB/B45606-EV1                |                          |                         |                          |  |
|                               | Reducer                                                  |                                         | Kawasaki M5X180CHB-10A-6RA/265-<br>RG20D25 |                          |                         |                          |  |
|                               | Movable boom cylinder                                    |                                         | Zhongxing ZXSMHW40.1.3                     |                          |                         |                          |  |
|                               | Stick cylinder                                           |                                         | Zhongxing ZXWMHW40.1.4                     |                          |                         |                          |  |
|                               | Maximum system pressure                                  |                                         | 32MPa                                      |                          |                         |                          |  |
|                               | Hydraulic oil tank                                       |                                         | 340L                                       |                          |                         |                          |  |
| Slewing mechanism             | Slewing bearing                                          |                                         | Sauter SSF1405.50CWHII                     |                          |                         |                          |  |
|                               | Maximum slewing speed                                    |                                         | 8rpm                                       |                          |                         |                          |  |
| Operation cabin               | Lifting                                                  | height                                  | 2650mm                                     |                          |                         |                          |  |
|                               | Boom specification                                       |                                         | 11m                                        |                          | 14m                     |                          |  |
| Operation basic<br>parameters |                                                          |                                         |                                            |                          | Movable bo              | om: 8.6m                 |  |
|                               |                                                          |                                         |                                            | 4.5 m                    | Stick: 6m               |                          |  |
|                               | Assembly hinge point of boom in the slewing platform     |                                         | Upper<br>hinge<br>point                    | Nether<br>hinge<br>point | Upper<br>hinge<br>point | Nether<br>hinge<br>point |  |
|                               | Maximum working radius                                   |                                         | 10.5m                                      | 10.5m                    | 13.5m                   | 13.5m                    |  |
|                               | Maximum working height                                   |                                         | 10.5m                                      | 12m                      | 13.5m                   | 15m                      |  |
|                               | Maximum working reach                                    |                                         | -3m                                        | -1.5m                    | -6m                     | -3m                      |  |
|                               | Theoretical load on maximum radius point(including grab) |                                         | 6t                                         | 6t                       | 3.9t                    | 4t                       |  |


#### YELLO EQUIPMENT


P: 1300 093 556 W: YELLOEQUIPMENT.COM




# SWHC45 PRODUCT SPECIFICATIONS

#### Working range





The diagram of dimension



|                    | The length of movable hinge point | The length of stick point | L      | H1    | H2    |
|--------------------|-----------------------------------|---------------------------|--------|-------|-------|
| Boom combination 1 | 7m                                | 4.5m                      | 11m    | 3.31m | 2.76m |
| Boom combination 2 | 8.6m                              | 6m                        | 12.58m | 3.31m | 2.76m |

#### YELLO EQUIPMENT

P: 1300 W: YELLOEQUIPMENT.COM

