

SMHW30

PRODUCT SPECIFICATIONS



YELLOTM
EQUIPMENT



SCAN
QR CODE FOR
PRODUCT INFO

STANDARD FEATURES

- Engine: Mitsubishi D06FRC-TAA
- Wide Working Range
- High Efficiency
- Low Fuel Consumption
- Max Travelling Speed 20km/h
- Rotating Speed 8R/Min
- Working Reach - 11.5m
- Max Cabin View Height 6.2m

- Rated Power
147 kW /2100 rpm
- Working Reach
11.5m
- Overall Weight
33,000 kg
- Gradeability
35%

YELLO EQUIPMENT

SANY AUTHORISED DEALER

P: 1300 093 556 W: YELLOEQUIPMENT.CO

YELLOTM
EQUIPMENT



Brief Introduction



Sany 30t Material Handling machine mainly apply to various bulk cargoes grab operation. The whole machine is light and flexible, stable, efficient.

CONFIGURATION PARAMETER


Power system	Engine	Model	Mitsubishi D06FRC-TAA
		Power	147kW/2100rpm
		Torque	750Nm//1350rpm
		Emission	CHN III
		Oil tank	465L
Chassis	Tread width		2387mm
	Wheelbase		2800mm
	Vertical span		4720mm
	Horizontal span		3953mm
	Turning radius		8600mm
	Maximum travel speed		20km/h
Hydraulic system	Control type		Electronic control positive flow system
	Main pump	Model	Rexroth A28VO130E71CPB/10DRVG3R12F1B2S40-0
		Rated flow	2X260L/min
	Main valve		Kawasaki KMX15RB/B45606-EV1
	Reducer		Sauter GS14D20C.0
	Movable boom cylinder		Hengli JSY26.5-DB
	Stick cylinder		Zhongxing ZX200.3.1B
	Maximum system pressure		32MPa
Hydraulic circuit		230L	
Slewing mechanism	Slewing bearing		Sauter SSF1405/40CWH II
	Maximum slewing speed		8rpm
Operation Cabin	Lifting height		2650mm
Operation basic parameter	Boom specification		12m
			Maximum working radius
			Maximum working height
	Maximum working reach		11.5m
	Maximum working height		12m
	Maximum working depth		-3 m
	Theoretical load on maximum radius point(including grab)		5t

SWHW48 PRODUCT SPECIFICATIONS

Working range



The diagram of dimension



	The length of movable hinge point	The length of stick point	L	H1	H2
Boom combination(standard)	6.8m	5.6m	5.85m	3.61m	3m

YELLO EQUIPMENT

SANY AUTHORISED DEALER

P: 1300 093 556

W: YELLOEQUIPMENT.COM

YELLOTM
EQUIPMENT